

## Pneumatic sealless steel strapping tool

---



### Characteristics

---

Strapping qualities:		Uniflex and Ultraflex max. 1100 N/mm <sup>2</sup> / 160'000 psi
Strapping dimensions:	widths	9.5 – 20.0 mm / 3/8 – 3/4"
	thicknesses	0.38 – 0.63 mm / .015 - .025"
Weights:		10.0 kg / 22.0 lbs without suspension
		10.5 kg / 23.2 lbs with suspension
Average seal strength:		approx. 80 %
Strap tension:		The tool is available for four different stages for strap tension, see chart
Suspensions:		Universal suspension bracket is supplied with the tool

### Advantages

---

- Ideal pneumatic tool to strap flat packages – high reliability eliminates down-time
- Pneumatic operation offers considerable time savings
- Air-motor for tensioning allows high and constant strap tension
- The sealless joint reduces the overall strapping costs by approx. 10% through the elimination of the seals

**Chart of types model A384**

Item No.	Model	Strap widths		Thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/s	inch/s
13.6810	A384/9.5/0.38-0.50/3.5	9.5	3/8"	0.38-0.50	.015-.020	3500	780	120	4.7
13.6811	A384/9.5/0.38-0.50/2.2	9.5	3/8"	0.38-0.50	.015-.020	2200	495	190	7.5
13.6820	A384/10/0.38-0.50/3.5	10		0.38-0.50	.015-.020	3500	780	120	4.7
13.6821	A384/10/0.38-0.50/2.2	10		0.38-0.50	.015-.020	2200	495	190	7.5
13.6830	A384/12.7/0.38-0.50/3.5	12.7	1/2"	0.38-0.50	.015-.020	3500	780	120	4.7
13.6831	A384/12.7/0.38-0.50/6.5	12.7	1/2"	0.38-0.50	.015-.020	6500	1460	65	2.5
13.6832	A384/12.7/0.58-0.63/3.5	12.7	1/2"	0.58-0.63	.020-.025	3500	780	120	4.7
13.6833	A384/12.7/0.58-0.63/6.5	12.7	1/2"	0.58-0.63	.020-.025	6500	1460	65	2.5
13.6834	A384/12.7/0.38-0.50/2.2	12.7	1/2"	0.38-0.50	.015-.020	2200	495	190	7.5
13.6835	A384/12.7/0.38-0.50/4.1	12.7	1/2"	0.38-0.50	.015-.020	4100	920	100	4.0
13.6836	A384/12.7/0.58-0.63/2.2	12.7	1/2"	0.58-0.63	.020-.025	2200	495	190	7.5
13.6837	A384/12.7/0.58-0.63/4.1	12.7	1/2"	0.58-0.63	.020-.025	4100	920	100	4.0
13.6840	A384/13/0.38-0.50/3.5	13		0.38-0.50	.015-.020	3500	780	120	4.7
13.6841	A384/13/0.38-0.50/6.5	13		0.38-0.50	.015-.020	6500	1460	65	2.5
13.6842	A384/13/0.58-0.63/3.5	13		0.58-0.63	.020-.025	3500	780	120	4.7
13.6843	A384/13/0.58-0.63/6.5	13		0.58-0.63	.020-.025	6500	1460	65	2.5
13.6844	A384/13/0.38-0.50/2.2	13		0.38-0.50	.015-.020	2200	495	190	7.5
13.6845	A384/13/0.38-0.50/4.1	13		0.38-0.50	.015-.020	4100	920	100	4.0
13.6846	A384/13/0.58-0.63/2.2	13		0.58-0.63	.020-.025	2200	495	190	7.5
13.6847	A384/13/0.58-0.63/4.1	13		0.58-0.63	.020-.025	4100	920	100	4.0
13.6850	A384/16/0.38-0.50/3.5	16	5/8"	0.38-0.50	.015-.020	3500	780	120	4.7
13.6851	A384/16/0.38-0.50/6.5	16	5/8"	0.38-0.50	.015-.020	6500	1460	65	2.5
13.6852	A384/16/0.58-0.63/3.5	16	5/8"	0.58-0.63	.020-.025	3500	780	120	4.7
13.6853	A384/16/0.58-0.63/6.5	16	5/8"	0.58-0.63	.020-.025	6500	1460	65	2.5
13.6854	A384/16/0.38-0.50/2.2	16	5/8"	0.38-0.50	.015-.020	2200	495	190	7.5
13.6855	A384/16/0.38-0.50/4.1	16	5/8"	0.38-0.50	.015-.020	4100	920	100	4.0
13.6856	A384/16/0.58-0.63/2.2	16	5/8"	0.58-0.63	.020-.025	2200	495	190	7.5
13.6857	A384/16/0.58-0.63/4.1	16	5/8"	0.58-0.63	.020-.025	4100	920	100	4.0
13.6860	A384/19/0.50-0.63/3.5	19	3/4"	0.50-0.63	.020-.025	3500	780	120	4.7
13.6861	A384/19/0.50-0.63/6.5	19	3/4"	0.50-0.63	.020-.025	6500	1460	65	2.5
13.6862	A384/19/0.50-0.63/2.2	19	3/4"	0.50-0.63	.020-.025	2200	495	190	7.5
13.6863	A384/19/0.50-0.63/4.1	19	3/4"	0.50-0.63	.020-.025	4100	920	100	4.0
13.6870	A384/20/0.50-0.63/3.5	20		0.50-0.63	.020-.025	3500	780	120	4.7
13.6871	A384/20/0.50-0.63/6.5	20		0.50-0.63	.020-.025	6500	1460	65	2.5
13.6872	A384/20/0.50-0.63/2.2	20		0.50-0.63	.020-.025	2200	495	190	7.5
13.6873	A384/20/0.50-0.63/4.1	20		0.50-0.63	.020-.025	4100	920	100	4.0

UNI = Uniflex regular duty strapping max. 850 N/mm<sup>2</sup> / 123'000 psi / ULT = Ultraflex high tensile strapping max. 1100 N/mm<sup>2</sup> / 160'000 psi