

Chart of types strapping head MH610

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension	
		mm	inch	mm	inch	N	lbs
47.5621	MH611/19/0.80-1.53/7.0/PET	19	¾	0.80-1.53	.031-.060	7000	1545
47.5623	MH611/25/0.60-1.35/7.0/PET	25	1	0.60-1.35	.024-.053	7000	1545
47.5625	MH611/32/0.60-1.35/7.0/PET	32	1¼	0.60-1.35	.024-.053	7000	1545

Features

- Compact and modular design
- One piece of aluminium cast housing
- High strap tension up to 7000N (1545 lbs) adjustable
- 19mm, 25mm or 32mm strap width usable, adjustable without changing parts
- Strap guide open feature
- Well proven separate feeding, tensioning and friction weld sealing systems
- High consistent seal efficiency because of environment temperature monitoring
- Use of state-of-the-art manufacturing, controlling and material technology
- Three side suspension points and plug connections for easy integration
- Long life and maintenance friendly, resulting in high availability

Options

- Dispenser for jumbo-coils
- Sword
- Telescopic arch
- Movable machine
- Side sealing machine
- Head suspension with power floating system
- Edge protection feed systems top and bottom
- Bunk feed system with various magazines
- Vertical and lateral press systems up to 80 KN
- Conveying systems
- Turntable for cross strapping
- Mechanical pack detectin sensor
- Thinner or rubber coated base protection plate
- Strap guide arch systems
- Control
- Cycle counter inside the head
- Dust cleaning system
- Counter