

The new generation machine enhanced model

**Characteristics**

Strapping qualities:	Polypropylene (PP)	
Strapping dimensions:	widths	5.0 – 13.0 mm
	thicknesses	0.45 – 0.65 mm
Strapping tension:	adjustable, 80 – 450 N	
Sealing method:	heat welding	
Power supply:	230V / 50Hz, 1 phase	
Power consumption:	0.3 kWh	
Strapping speed:	2.5 sec./cycle (approx. 24 strapping cycles/min.)	
Dimensions:	length	850 mm
	width	560 mm
	table height	780-950 mm adjustable
Weight:	70 kg	
Max. package weight:	80 kg	
Min. package size:	80W x 20H mm	
Strap core inner diameter:	200 / 230 / 280 mm (interchangeable)	
Temp. of working environment:	5 ~ 40°C	

Advantages

- Light, compact design
- Easy operation, simple maintenance
- CE certified
- Compact mechanical control head with 30% less moving parts
- Hinged stainless top plate
- Electronic outside tension control
- Sensor controlled heater
- Rigid castors with brake
- Automatic motor stop to save energy
- Reliable P.C. board electric control
- Adjustable table height from 780 to 950 mm
- Proven quality
- Interchangeable strap core inner diameter from 200 mm to 280 mm
- Safety limit switch included

Chart of types model PM207

Item No.	Model
44.2050	PM207